



Elevator 1xSchuko 2xEuro	Elevator 1xSchuko 2xEuro
<p>Beschreibung:</p> <ul style="list-style-type: none"> • Versenk- und herausfahrbare Elektrifizierungseinheit für den Einbau in Küchenarbeitsplatten wie Holz, Schichtstoff, Naturstein oder Glas bzw. in Bürotische. • Nach leichtem Druck auf den Deckel fährt die Einheit dank eines Federmechanismus aus und bietet eine komfortable und sichere Stromzufuhr über eine Schutzkontakt- und zwei Euro-Steckdosen. • Einfaches und flächenbündiges Versenken bei Nichtgebrauch. • Befestigung mittels Schraubring. 	<p>Description:</p> <ul style="list-style-type: none"> • Ascending and descending electrification unit for installation for kitchen worktops like wood, laminated plastic, natural stone or glass resp. in office and conference tables. • When pushing the lid the unit ascends due to a spring mechanism and offers a convenient and safe power supply via one German type and two Euro type sockets. • Simple and plain descending when not used. • Mounting via ring nut.
<p>Steckdosen:</p> <ul style="list-style-type: none"> • Nach IEC 60884, VDE 0620-1 • 2-polig mit Schutzkontakt • 16A/3680W (Schuko) und 2,5A/625W (Euro), AC250V, IP20, mit Kinderschutz • Schwarz 	<p>Sockets:</p> <ul style="list-style-type: none"> • According IEC 60884, VDE 0620-1 • 2-pole with earthing contact • 16A/3680W (Schuko) and 2,5A/625W (Euro), AC250V, IP20, with child protection • Black
<p>Anschluss:</p> <ul style="list-style-type: none"> • 2,0m H05VV-F 3G1,5mm² schwarz mit offenen Enden und Aderendhülsen 	<p>Connection:</p> <ul style="list-style-type: none"> • 2,0m H05VV-F 3G1,5mm² black with endsleeves • German type mounting plug black enclosed

<ul style="list-style-type: none"> Mit beigelegtem Schutzkontakt-Montagestecker schwarz 	
Befestigung: <ul style="list-style-type: none"> In rundem Ausschnitt mit $\varnothing 80\text{mm}$ (+/-1mm) Für Plattenstärken von 16mm bis 60mm Fixierung über Schraubring 	Mounting: <ul style="list-style-type: none"> In round hole with $\varnothing 80(+/-1)\text{mm}$ For mounting in plates with thicknesses from 16mm to 60mm Mounting via ring nut.
Material: <ul style="list-style-type: none"> Kunststoff: Schwarz, PA6 GF 30 V1 , Glühdraht-Prüfung bis 850°C Profil: Aluminium glänzend poliert, „Edelstahl-Look“, Strangguss Blenden: Edelstahl gestanzt und gebürstet 	Material: <ul style="list-style-type: none"> Plastic: Black, PA6 GF 30 V1 , glow wire resistant up to 850°C Profile: Aluminum polished "stainless steel look", continuous casting Aperture: Stainless steel brushed and stamped
Abmessungen in mm: <ul style="list-style-type: none"> Siehe Zeichnung 	Measurements in mm: <ul style="list-style-type: none"> According to drawing
Lieferform: <ul style="list-style-type: none"> In Kartonbox verpackt 	Packing: <ul style="list-style-type: none"> In carton box
Lieferumfang: <ul style="list-style-type: none"> 1x Elevator 1x Montageanleitung 	Extent of delivery: <ul style="list-style-type: none"> 1x Elevator 1x Mounting instruction