

## Datasheet

Art.No. 92.030.5958.1

Intermediate coupling GST18i3Z 1P1 SW

Intermediate coupling, GST18i3, 3 pole, 1 input, 1 output, 250 V, 20 A, for direct routing, colour of coding: black



Art.No.	92.030.5958.1
EAN	4015573236820
Order unit	1 pieces

## Approvals



## Technical data

### General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	No
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE

### Model

Number of poles	3
Number of inputs	1
Number of outputs	1
Type of fastening	No
Degree of protection (IP)	IP20
Type of distributor	Intermediate coupling


**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

**Dimensions**

Length	39 mm
Width	28.2 mm
Height	13 mm

**Classification**

ECLASS 8.1	27440603: Compact distributor for plug-in building installation
ETIM 5.0	EC002567: Compact distributor for plug-in building installation
ETIM 4.0	EC002567: Compact distributor for plug-in building installation
ETIM 3.0	

Drawings

